PROVO PART NUMBER **99422-21WH**	**PLENUM TYPE "Z" SOLID BARE COPPER CONDUCTORS CONDUCTORS TWISTED • RIP CORD PLENUM PVC INSULATION • WHITE PLENUM PVC JACKET -20°C +60°C**



SPEC CRITERIA	SPECIFICATION
AWG	22
STRANDING	SOLID
NUMBER OF CONDUCTORS	4
INSULATION TYPE	PLENUM PVC
INSULATION THICKNESS	0.008"
JACKET TYPE	PLENUM PVC
JACKET THICKNESS	0.016"
NOM. CABLE OD	0.127"
VOLTAGE	300
TEMPERATURE	-20°C to +60°C
PUT-UP METERS	300
WEIGHT (LBS)	12
CSA	**CMP, FT-6**
UL	**CMP C22.2, UL444**
RoHS	**COMPLIANT**
FLAME TEST	**FT-6**
AVAIL. JACKET COLOURS	Grey / White / Red / Violet
COLOUR CODE	Red / Green / Yellow / Black

©2022 PROVO LTD.
Provo makes every reasonable effort to ensure their accuracy at the time of this publication. Information and specifications herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. The information provided is correct to the best of Provo's knowledge, and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes part of. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. All sales of Provo products are subject to Provo's standard terms and conditions of sale.