PÉRIPHÉRIQUES

NCoder

Le NCoder permet aux opérateurs des systèmes de contrôle d'accès intelligents Salto d'attribuer, de modifier et d'invalider rapidement des identifiants physiques grâce à une solution d'encodage intuitive et dédiée. Les opérateurs et les administrateurs système peuvent ajouter rapidement et en toute sécurité des identifiants d'accès intelligent codés de manière sécurisée.



Fonctionnalités

- Facilité d'utilisation, avec un outil de programmation simple et rapide pour les identifiants RFID qui met la configuration, la modification et l'invalidation des identifiants RFID intelligents physiques à portée de main.
- Compatible avec une large gamme de technologies de badges RFID*.
- Connectivité avec la dernière technologie de contrôle d'accès intelligent, basée sur nos meilleures technologies de données Salto SVN dans le badge, BLUEnet Radio-Fréquence et JustIN Mobile.
- Sécurité renforcée garantie, grâce à un algorithme chiffré hautement sécurisé pour traiter et coder les badges.
- Les données SAM du lecteur/encodeur standardisé ne sont pas stockées dans le dispositif afin de garantir un système de gestion des clés sécurisé.


* Sécurité renforcée garantie, grâce à la technologie de badge intelligent DESFire hautement sécurisée pour traiter et coder les badges pour Homelok.

Caractéristiques techniques

- Dimensions : 95,5 mm x 141 mm x 30,5 mm
- Communications protégées par cryptage standard (DTLSv1.2 – AES128).
- Matériau du capot : PC/ASA
- Consommation électrique : 5 V
- Adressage IP par DHCP.
- Connexion au PC : USB ou Ethernet*, simplifiant les exigences en matière de source d'alimentation et permettant une connectivité facile à l'infrastructure de sécurité existante.

*Selon le modèle et la plateforme.

Schémas techniques



Plateformes technologiques

Salto Space

Réseau sur site

Salto Homelok

Application cloud

Copyright @ 2026 SALTO Systems S.L. All rights reserved

Technologies radio-fréquence

RFID NFC Bluetooth

Certifications

Supports



Badge

NXP MIFARE®
HID®



Médaillon

NXP MIFARE®



Clé Digitale

Bluetooth LE
NFC – Near Field Communication

Copyright @ 2026 SALTO Systems S.L. All rights reserved

Clause de non-responsabilité:

For a complete description of the product range, verification of the availability and technical feasibility of the selected product, and a commercial offer, please get in touch with the local authorized Salto dealer or a Salto office.

Salto reserves the right to modify the product and its components.

Technical information and images displayed on the Salto product page are for informative purposes only and designed to inform about the main product features, options and technical specifications. Therefore, all images, illustrations, shapes, features, specifications, sizes, data, descriptions and colours shown on the Salto Systems page shall consider as no-binding approximate indications only.

Part of the content of this document may have been generated or assisted by artificial intelligence tools. This document may also include automatic or manual translations provided exclusively for informational purposes, which may contain errors or inaccuracies. Salto does not guarantee the accuracy, quality, or reliability of such content or translations, including those generated by AI.

The User is responsible for verifying the information contained in this document and, in case of doubt, must refer to the original English version, which shall prevail in the event of any discrepancy. Other language versions are provided for informational purposes only.

Although Salto makes reasonable efforts to review the content of its downloadable documents, they may contain errors or omissions. Salto assumes no liability arising from the User's use, interpretation, or decisions made based on the information contained in this document, which is used at the User's sole responsibility.

For more detailed information on the use of artificial intelligence, translations, and applicable limitations of liability, please refer to the "Terms of Use of our Website".

Copyright @ 2026 SALTO Systems S.L. All rights reserved